



GEOTREE **Henkel**
LOCTITE

NJWEA 2025 FALL TECHNOLOGY TRANSFER SEMINAR
WED OCT 22ND 2:10 – 2:50 PM

GEOPOLYMER OR NOT GEOPOLYMER
... THAT IS THE QUESTION

1

WELCOME TO GEOTREE'S WEBINAR

SCOTT NAIVA, P.E.; MBA – PRESENTER



- Northeast Region Manager for GeoTree Solutions (11 yrs)
- B.S. in Civil Engineering from Syracuse University, NY
- MBA from Eastern University, Saint Davids PA
- 36 Years of Engineering Consulting and Business Development Engineering Sales Experience
- Past Board Member of Mid Atlantic Society for Trenchless Technologies (MASTT)
- Active member in 4 Regional Water Environment Association Collection Committees

Scott Naiva, P.E.; MBA Northeast Region Manager, Wayne PA
Scott.Naiva@Henkel.com; c: 610-971-0362



2

OUTLINE OCT 2025

- **What is a geopolymer? Why is this important?**
 - Flexural Strength, corrosion resistance, self bonding
- **How to design a geopolymer liner**
 - Design method – Distributed Beam WRC -Approved
 - Applies to apples bid documents
- **Case Studies**
 - (BWSC) New Boston Main Interceptor and Canal Street
 - Pittsburg Water Sewer Authority (PWSA)
 - Richmond Virginia Marshall Street -1900' of 60" diameter brick pipe
 - Narragansett Bay Commission (NBC) Brick Pipe Rehab Route 6 & 10 Interchange
 - DC Water, NJ B Street (18' diam pipe) & Lower Area Trunk Sewer (42" diam pipe)
 - DelDOT – Three Large Plate Steel Culvert up to ~17' Span (Corrugations Filled)
 - PennDOT I84 – VE saves \$3,000,000; Saves 8 acres of trees, 4000' access roads
 - PennDOT I95 – Philadelphia Water Dept (PWD) ~2100' 93" Brick Pipe
- **Calculators** - Thickness Design Calculators Pipe and Manhole



3

GEOPOLYMER LINING SYSTEM (GLS) CONSTRUCTION & ALTERNATIVES



4


NJWEA - Fall Tech Transfer 2025 Trenchless Technologies

STRUCTURAL - GEOPOLYMER LINING SYSTEM (GLS)



5

STRUCTURAL - GEOPOLYMER LINING SYSTEM (GLS)



6

GEOPOLYMER MIXING AND PUMPING



7




8

GEOPOLYMER SHOTCRETE APPLICATION



9

GEOPOLYMER LINING SYSTEM (GLS)



10

INTERNAL BYPASS



INLET SUMP



INCOMPLETE INVERT



COMPLETED INVERT

11

GLS - SMALL CONSTRUCTION FOOTPRINT



12

GLS – SMALL CONSTRUCTION FOOTPRINT



Small equipment footprint allows for flexibility & planning around client needs.



13

101" BRICK ARCH PIPE



Near Busway



Small Construction Footprint



14

CIPP OVER THE HOLE WET OUT: FOOTPRINT



10' Diameter CIPP Wet Out Footprint – 3 to 4 traffic lanes



15

TRENCHLESS TECHNOLOGY ALTERNATIVE SUMMARY

CIPP




PAVED INVERT

GEOPOLYMER LINING SYSTEM (GLS)



SLIP LINE


REINFORCED OPC SHOTCRETE



SPIRAL




16



GEOPOLYMER BASIC MATERIAL PROPERTIES

TEC talks




17

COMPARISON OF ORDINARY PORTLAND CEMENT (OPC) WITH GEOSPRAY AND GEOSPRAY HCE

| Test Method / Description | Duration | Ordinary Portland Cement (OPC) | GeoSpray Geopolymer | GeoSpray HCE Geopolymer |
|--|----------|--------------------------------|--|-------------------------|
| Compressive Strength ASTM C39 / C109 (psi) | 28 days | 5,000 | 8,000 psi | |
| Flexural Strength ASTM C78 (psi) | 28 days | 500 psi | 1,500 psi | |
| X-Ray Fluorescence (XRF) testing ASTM C114 is used to verify 70% minimum of pozzolanic material composed of SiO ₂ , MgO, Al ₂ O ₃ , or Fe ₂ O ₃ | N/A | No - usually 0 to 10% | Yes - only geopolymers have over 70% | |
| Carbon Footprint (Manufacturing) | N/A | * | * 65% to 90% less than OPC (Davidovits 2011) | |
| Chemical Corrosion Resistance DIN 19573 | Varies | Pass XWW2 ? | Pass XWW3 | Pass XWW4 |

TEC talks



18

WHAT IS A GEOPOLYMER?

Not a Plastic


- Not HDPE / PVC / Epoxy


Looks and feels like cement

- Workability
- Material Properties
- Service Life


Chemical structure like natural stone

- Monolithic
- Durable
- Corrosion Resistant






TEC talks




19

GEOPOLYMER CHEMISTRY PRIMER




Typical Hydrated Ordinary Portland Cement (OPC) Structure



Typical Geopolymer Structure

TEC talks



20

SELF BONDING



↑
Joint in Tested Sample

GeoSpray Geopolymer



Portland Based Material



Day 0 Day 1 Day 7 Day 14 Day 28



21


CHEMICAL ACID RESISTANCE TESTING ASTM C-267 (MICROBIAL INDUCED ACID CORROSION)

Aerobic H_2SO_4 Production and Corrosive Attack Above Water Line

↑
 H_2S Gas Emission


Anaerobic Generation of H_2S Below Water Line in Septic Effluent

GeoSpray




Day 0 Day 84

Portland




Day 0 Day 84



4 X better

ASTM C-267: 2" cubes soaked in 7% sulfuric acid (pH =9) for 84 days before & after



22

CHEMICAL RESISTANCE TESTING ASTM C-267-01 TESTING PARAMETERS NEEDS TO BE DEFINED



Chemical (including concentration):
 1% Sulfuric Acid – pH 1.3
 7% Sulfuric Acid – pH 0.9

Type & size of sample: 2" cubes
 Maturity (time of cure) 28 Days Cure

Volume of test solution (excess solution will cause large differences in results) 2 Liter per container

Size of container
 10" wide x 7" long x 2.5" deep
 12 samples per container

Time between changing test solution
 1,7,14,28 and 56 -days

23


CHEMICAL RESISTANCE CORROSION TEST DIN 19573

Exposure Service Level XWW1 to XWW3

- Constant pH 4 for 4000 hrs
- GeoSpray Passes XWW3
- GeoSpray for below 10ppm H_2S


Exposure Service Level XWW4

- Constant pH 1 for 70 days – 75% Residual Compressive Strength
- Constant pH 0 for 14 days – 55% Residual Compressive Strength
- GeoSpray HCE Passes XWW4
- GeoSpray HCE Certified for Highest Level >10 ppm H_2S




GeoSpray (Soaked in Water)

GeoSpray (4000 hrs, pH 4)




14 days H2SO4 storage pH0

unbrushed water storage brushed



water storage H2SO4 pH 0 (14d)



24




DESIGN METHODOLOGY


TEC talks

GEO TREE


25

5 SPRAY - ON DESIGN METHODS, SEE PAPERS




2016 Laboratory Testing and Analysis of Geopolymer Pipe-lining: Technology for Rehabilitation of Sewer & Storm Water Conduits 

2017 Part II – CMP Culvert Analysis



2019 Laboratory Testing and Analysis of Geopolymer Pipe-lining Technology for Rehabilitation of Sewer & Storm Water Conduits





NASTT No Dig Paper WM-T6-03 (2016) – Royer & Allouche
 NASTT No Dig Paper TM2-T3-04 (2017) – Royer & Iseley
 TRB 2019 – Royer & Matthews

GEO TREE TEC talks

26

LA TECH – TTC: EXPERIMENTAL PARAMETERS






GEO TREE TEC talks

27

RCP DATA –VS- 5 MODEL PREDICTIONS - 48" PIPE


Comparison of Model Thickness Predictions to Scaled D-Load
 Test Data for RCP Pipes using $B_f=1.5$ at 48 Inch Diameter



| Design Load (psi) | D-Load*Bf (in) | Crack 0.01 (in) | Bazant-Cao (in) | Distributed Beam (in) | Crack 0.0625 (in) | Roark's (in) |
|-------------------|----------------|-----------------|-----------------|-----------------------|-------------------|--------------|
| 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 50 | 0.5 | 1.5 | 1.0 | 0.8 | 0.6 | 0.5 |
| 100 | 1.0 | 2.5 | 1.5 | 1.2 | 0.9 | 0.7 |
| 150 | 1.5 | 3.5 | 2.0 | 1.5 | 1.1 | 0.8 |
| 200 | 2.0 | 4.5 | 2.5 | 1.8 | 1.3 | 0.9 |
| 250 | 2.5 | 5.0 | 3.0 | 2.1 | 1.5 | 1.0 |
| 300 | 3.0 | 5.5 | 3.5 | 2.4 | 1.7 | 1.1 |
| 350 | 3.5 | 6.0 | 4.0 | 2.7 | 1.9 | 1.2 |


Thickness (in)

Design Load (psi)


Distributed Beam Model
 - good choice - not over or under conservative &

GEO TREE TEC talks

28



29



30

BWSC – 2021 CIP REHAB OF LARGE DIAMETER SEWER MAINS CITY PROPER & SOUTH BOSTON

TEC talks

TRENCHLESS TECHNOLOGY CENTER.

1/10/23 Boston Municipal Forum

31


BWSC PROJECT LINING TYPES

| Diameter (in.) | CIPP (LF) | GLS (LF) OPC with Epoxy | Total / % Complete |
|-------------------|-------------|---------------------------------------|--------------------|
| 15" to 18" | 827 | | |
| 36" & 30" x 36" | 440 | | |
| Manholes 48" | | 1009 | |
| 48" Pipe | | 951 | |
| 60" & x 57" x 60" | | 501 | |
| 66" | 370 | 1825 - 370 = 1455 | |
| Total | 1637 | 3916 | 5553' / 56% |

32



33



34

OPTIONS CONSIDERED

Dig and Replace

- Expensive, longer construction window, greater impact to environment

Slip Lining

- Needed insertion pit and decreased hydraulic capacity, \$\$\$

Cured in Place Pipe (CIPP)

- Permitted on bid for 15", 18" & 36" pipe. Change order for and 370' of 66" Pipe
- Good option on smaller pipes, variable option for larger pipe requiring MH cover removal & external bypass

Geopolymer Lining System (GLS)

- Selected for small footprint, thin liner & improved hydraulics, internal bypass, excellent corrosion and scour protection, no MH cover removal, lack of cold joints

Ordinary Portland Cement (OPC) with 125 mil Epoxy

- Permitted on bid but not selected, similar GLS benefits but weaker strength required greater thickness and poor corrosion resistance required 125 mil epoxy, cold joints in concrete



35



36

NJWEA - Fall Tech Transfer 2025 Trenchless Technologies



37



38



39



40

NJWEA - Fall Tech Transfer 2025 Trenchless Technologies




41



42




43




44

NJWEA - Fall Tech Transfer 2025 Trenchless Technologies




45



46






47





48

GEOPOLYMER OR NOT GEOPOLYMER?
ANS. - DEPENDS

| Item to complete 370' of 66" Diam. | Geopolymer | CIPP |
|------------------------------------|------------|-----------|
| Internal construction | Y | N |
| Safety | Varies | Varies |
| Internal bypass | Y | N |
| Bypass length (ft) | 370' | 370+ 100' |
| Cure Time to return flow (hr) | 2 | 32-36 |
| Small Footprint | Y | N |
| Dusty | Y | N |
| Styrene Smell | N | Y |
| Remove MH top | N | Y |
| Repave | N | Y |
| Impact to public | Smaller | Greater |
| Set Up Shifts | 2 | 4 |
| Lining Shifts | 6 | 4 |
| Clean up / Restoration Shifts | 1 | 2 |
| Total # of 8 hr Shifts | 9 | 10 |
| COSTS | Depends | Depends |

49

CITY OF RICHMOND



PWSA LDSR 2020- 2025

PITTSBURGH WATER SEWER AUTHORITY – LARGE DIAM. SEWER REHAB




50



2020 LDSR Construction -Geopolymer Lining System (GLS)


NASTT.ORG NASTT 2024 No-Dig Show educate · train · research · publish

51

101" Brick Arch Pipe Location

Near Busway



Small Construction Footprint

NASTT.ORG NASTT 2024 No-Dig Show educate · train · research · publish

52

NJWEA - Fall Tech Transfer 2025 Trenchless Technologies

Mixing Operations at Busway



16% - 20% Water

Polypropylene Fibers

NASTT.ORG

NASTT 2024 No-Dig Show

educate · train · research · publish

53



NASTT.ORG

NASTT 2024 No-Dig Show

educate · train · research · publish

54



Sep 16, 2022 8:26:07 AM
Zoo North lot

NASTT.ORG

NASTT 2024 No-Dig Show

educate · train · research · publish

55





NASTT.ORG

NASTT 2024 No-Dig Show

educate · train · research · publish

56

CITY OF RICHMOND MARSHALL ST. 60" BRICK SEWER GEOPOLYMER REHABILITATION



57

CITY OF RICHMOND MARSHALL ST. 60" BRICK SEWER GEOPOLYMER REHABILITATION




58

CITY OF RICHMOND MARSHALL STREET 60" BRICK SEWER GEOPOLYMER REHABILITATION


Project Details:

- March-April 2019 Project completed in 6 weeks
- 1,900 feet of 60" brick CSO sewer
- 13 Brick MH – 20 to 22" Diameter Shafts 17' deep
- 1.5 MGD Dry Weather Flow
- Internal By-Pass utilized
- 1.5" of GeoSpray Geopolymer mortar on 60" Pipe
- 1" of GeoSpray Geopolymer mortar on Manholes



59

LIMITED 20 – 22" DIAMETER MH ACCESS



60

PIPE DEFECTS



61

LINING OPTIONS CONSIDERED

- **Dig and Replace**
 - Not ideal due to pipe locations (e.g. significant community impact) and cost.
- **Cured in Place Pipe (CIPP)**
 - Required MH removal / insertion pits making it \$\$\$\$. Large construction footprint with wet out process in limited area a challenge. Community impact concerns with larger disruption and styrene was not ideal.
- **Epoxy**
 - Access not an issue. Provides good corrosion resistance but expensive compared to other spray-on applications, and structural enhancement only, not stand alone.
- **Spiral (SPR)**
 - Limited access not an issue and application provides an adequate structural component, however, reduces capacity and \$\$\$ compared to spray-on applications.
- **Ordinary Portland Cement (OPC) Shotcrete**
 - Access not an issue. Estimated life-expectancy 1/3 to 1/2 that of geopolymer applications.
- **Geopolymer Lining**
 - **Strength and corrosion protection / longevity. No MH removal, small footprint, can do internal bypass without cold joint. Low cost alternative**

62

EVALUATION MATRIX 1900' OF 60" BRICK SEWER - GEOPOLYMER SELECTION

| Factor (1 -Worst & 4 Best) | Epoxy | CIPP | SPR | OPC Gunite | GeoSpray Geopolymer |
|---------------------------------|-----------|-----------|-----------|------------|---------------------|
| Above Ground Site Preparation | 3 | 1 | 4 | 3 | 4 |
| Bypass Pumping Requirements | 3 | 1 | 4 | 3 | 3 |
| Permit Requirements | 3 | 1 | 4 | 3 | 3 |
| Construction Duration | 2 | 1 | 3 | 4 | 3 |
| Maintain Existing Flow Capacity | 3 | 4 | 3 | 2 | 3 |
| 50 YR LifeCycle | 4 | 4 | 4 | 1 | 4 |
| Cost | 1 | 3 | 2 | 4 | 4 |
| Overall Scores | 19 | 15 | 24 | 20 | 24 |

63

EVALUATION MATRIX 1900' OF 60" BRICK SEWER - GEOPOLYMER SELECTION

| OPTION | Pipeline Rehab Cost / LF | Pipeline Rehab - for 1900' of Pipe | Internal Repairs Before Liner | Manhole Sinkhole and Misc | 15% Contingent | Initial Estimated Cost Total | 50 Yr Life Cycle Multiplier | 50 Yr Design Cost Total |
|---------------------|--------------------------|------------------------------------|-------------------------------|---------------------------|----------------|------------------------------|-----------------------------|-------------------------|
| Epoxy | \$1,998 | \$3,796,414 | \$250,000 | \$71,695 | \$617,716 | \$4,735,825 | 1 | \$4,735,825 |
| CIPP | \$1,227 | \$2,331,421 | \$150,000 | \$621,695 | \$465,467 | \$3,568,583 | 1 | \$3,568,583 |
| SPR | \$1,244 | \$2,363,400 | \$50,000 | \$77,695 | \$373,664 | \$2,864,759 | 1 | \$2,864,759 |
| OPC Gunite | \$502 | \$954,072 | \$250,000 | \$85,150 | \$193,383 | \$1,482,605 | 2 | \$2,965,211 |
| GeoSpray Geopolymer | \$500 | \$950,000 | \$250,000 | \$71,695 | \$190,754 | \$1,462,449 | 1 | \$1,462,449 |

64

NJWEA - Fall Tech Transfer 2025 Trenchless Technologies



65



66



67



68

HAND SPRAYING



Distance: 0.0
MMH: Manhole
Clock from:
Clock to:
Station:
S-01/L1
Dimension 1:
Dimension 2:
Remarks: 2



69

COMPLETED STRUCTURES



70

SPINCAST MANHOLE REHAB



71

**RI DOT / NARRAGANSETT BAY
COMMISSION (NBC)
REHABILITATION OF LARGE
DIAMETER BRICK SEWER WITH
GEOSPRAY GEOPOLYMER MORTAR**



72

GLS - SMALL CONSTRUCTION FOOTPRINT



73

GLS - SMALL CONSTRUCTION FOOTPRINT



Small equipment footprint allows for flexibility & planning around client needs.

74

GLS - SMALL CONSTRUCTION FOOTPRINT



75

GLS - SMALL CONSTRUCTION FOOTPRINT




76

CONSTRUCTION FOOTPRINT / PIPE ACCESS



77

INFILTRATION ISSUES



78

CROWN REPAIR & INFILTRATION CONTROL




79

LINED PIPE AT UNLINED MANHOLE



80

LINER THICKNESS / DEPTH GAUGES



81

VARIOUS PIPE SIZES OF REHAB



82

COMPLETED STRUCTURES



90 Degree bend with internal bypass

83

DC WATER, WASHINGTON DC 2 CASE EXAMPLES

84

NEW JERSEY B STREET, ON NATIONAL MALL

Wash. Monument

US Capitol

LEGEND

- Pipe Rehab Location
- Project Location Area
- Main and O St. Pumping Station

Pipe Rehabilitation Locations

GEO TREE **TEC talks**

85

MOBIL SCAFFOLDING – DOUBLE BENCH

GEO TREE **TEC talks**

86

PRESSURE WASHING AND SPRAYING GEOPOLYMER

GEO TREE **TEC talks**

87


TWO DC WATER PROJECTS

- New Jersey B Street**
 - 4300 LT of 10 to 18' Diameter Brick
 - Rehab Crown Only
- Lower Area Trunk Sewer (LAT)**
 - 12,000 LF of 42" Brick Rehab – choose CIPP or Geopolymer or Spiral

| Item No. | ITEM DESCRIPTION | Estimated Quantity | Unit | Unit Price | | Extension Amount | | Rehabilitation Method (Indicate one method below with an "X") | | |
|----------|--|--------------------|------|------------|-------|------------------|-------|---|----|-----|
| | | | | Dollars | Cents | Dollars | Cents | CIPP | GP | SPB |
| 19. | Sewer Lining from MH-51423 to MH-32867 | 1 | LS | | | | | NA | X | NA |
| 20. | Sewer Lining from MH-32867 to MH-32023 | 1 | LS | | | | | NA | X | NA |
| 21. | Sewer Lining from MH-32023 to MH-51422 | 1 | LS | | | | | NA | X | NA |



GEO TREE **TEC talks**

88



GEOPOLYMER OR NOT GEOPOLYMER?



ANS. - DEPENDS

| Item to complete 370' of 66" Diam. | Geopolymer | CIPP |
|------------------------------------|------------|-----------|
| Internal construction | Y | N |
| Safety | Varies | Varies |
| Internal bypass | Y | N |
| Bypass length (ft) | 370' | 370+ 100' |
| Cure Time to return flow (hr) | 2 | 32-36 |
| Small Footprint | Y | N |
| Dusty | Y | N |
| Styrene Smell | N | Y |
| Remove MH top | N | Y |
| Repave | N | Y |
| Impact to public | Smaller | Greater |
| Set Up Shifts | 2 | 4 |
| Lining Shifts | 6 | 4 |
| Clean up / Restoration Shifts | 1 | 2 |
| Total # of 8 hr Shifts | 9 | 10 |
| COSTS | Depends | Depends |

- 10,000 LF 30 IN.
- 50% / 50%

Q&A

89

GEOPOLYMER OR NOT GEOPOLYMER... THAT IS THE QUESTION

ANS. DEPENDS

Scott Naiva, P.E.
Scott.Naiva@Henkel.com
610-971-0362







Q&A







90